the and they find they and find the first

UTILITY PATENT APPLICATION **TRANSMITTAL**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 0100.0001320 Total Pages 28 First Inventor Terry M. LaViolette Title Method and Apparatus for Posting a Computer Having Multiple Video Adapters Express Mail Label No. EL504284831US

S. PTO	
5,5	27
JC836	
รั	

APPLICATION ELEMENTS	ADDRESS 10: Assistant Commissioner for Patents
See MPEP chapter 600 concerning utility patent	Box Patent Application Washington, DC 20231
application contents	
1. X Fee Transmittal Form	6. Nucleotide and/or Amino Acid Sequence
(Submit an original, and a duplicate for fee processing)	Submission (if applicable, all necessary)
2. ☑ Specification Total Pages 16	a. 🗌 Computer Readable Copy
(preferred arrangement set forth below)	 Daper Copy (identical to computer copy)
- Descriptive title of the Invention	c. Statement verifying identity of above
- Cross References to Related Applications	copies
 Statement Regarding Fed sponsored R & D Reference to Microfiche Appendix 	copios
- Background of the Invention	ACCOMPANIAL APPLICATION PARTS
- Brief Summary of the Invention	ACCOMPANYING APPLICATION PARTS
- Brief Description of the Drawings (if filed)	7. Assignment Papers (cover sheet & document(s))
- Detailed Description	8. 🛛 37 CFR 3.73(b) Statement 🔀 Power of
- Claim(s)	(when there is an assignee) Attorney
- Abstract of the Disclosure	English Translation Document (if applicable)
3. Drawings (35 USC 113) Total Sheets 3	10. Information Disclosure
4. Oath or Declaration Total Pages 3	Statement (IDS)/PTO-1449 IDS Citations
a. 🔯 Newly executed (original or copy)	11. Preliminary Amendment
b. 🔲 Copy from a prior application	12. Return Receipt Postcard (MPEP 503)
(37 CFR 1.63(d))	(Should be specifically itemized)
(for continuation/divisional with Box 17 completed)	13. Small Entity Statement filed in Prior
[Note Box 5 below] i. DELETION OF INVENTOR(S)	Statement(s) Application, Status still
Signed statement attached deleting	proper and desired.
inventor(s) named in the prior application,	14. Certified Copy of Priority Document(s)
see 37 CFR 1.63(d)(2) and 1.33(b).	(if foreign priority is claimed)
	15. Other
5. Microfiche Computer Program (Appendix)	
5. Microfiche Computer Program (Appendix)	
16 If a CONTINUING ADDITION	
16. If a CONTINUING APPLICATION, check app	ropriate box and supply the requisite information:
Continuation Divisional Continuation-in	
Prior Application Information: Examiner	Group / Art Unit.
17 000000000	DENOE ADDRESS
17. CORRESPONI	
Customer Number or Bar Code Label	or, 🔀 Correspondence Address Below
Markison & R	ackamn P.C
P.O. Bo	• •
Wacker	
Chicago, Illino	
Telephone: 312-939-9800	Facsimile: 312-939-9828
τοιεμασίε: 312-737-7000	F 4CSHIHIC. 314-737-7048

Name (Print/Type)	John R. Garrett	REGISTRATION NUMBER	27,888	
Signature	John R Yand	Date	July 27, 2000	
	/			



FEE TRANSMITTAL

Note Effective October 1, 1997 Patent fees are subject to annual revision

TOTAL AMOUNT OF PAYMENT (\$) 690.00

METHOD OF PAYMENT (check one)

1.

☐ The Commissioner is hereby authorized to charge indicated fees and credit any over payments to

	charge mulcated le	es and c	redit arry over payments to		
	Deposit Account N	umber	50-0441		
	Deposit Account Name	ATI	Technologies, Inc.		
☐ Charge Any Additional Fee Required Under 37 CFR 1 16 and 1 17 ☐ Charge the Issue Fee Set in 37 CFR 1 18 at the					
mailing of the Notice of Allowance 2. Payment Enclosed:					
	☐ Check	☐ Mon	ey Order 🗌 Other		

FEE CALCULATION

1. FILING FEE

Large Entity Fee Code		Small Fee Code	Fee (\$)	Fee Descriptio n	Fee Paid
101	690	201	345	Utility filing fee	690.00
106	310	206	155	Design filing fee	
107	480	207	240	Plant filing fee	
108	760	208	380	Reissue filing fee	
114	150	214	75	Provisional filing fee	

SUBTOTAL (1) (\$) 690.00

2. CLAIMS

_,,	•		
Claims	Extra	Fee from below	Fee Paid
Total 20	(20 =)		
Indep 3	(3 =)		
Multiple Dep			

Large Entity Entity			Fee Description
Fee	Fee		
(\$)	Code	•	
18	203	9	Claims in excess of 20
78	202	39	Independent claims in excess of 3
260	204	130	Multiple dependent claim
78	209	39	Reissue independent claims over original patent
18	210	9	Reissue claims in excess of 20 and over original patent
	Fee (\$) 18 78 260 78	Fee Fee (\$) Code 18 203 78 202 260 204 78 209	Fee Fee (\$) Code 18 203 9 78 202 39 260 204 130 78 209 39

Complete if Known

Application Number	
Filing Date	7/29/00
First Named Inventor	Terry M. LaViolette
Group Art Unit	
Examiner Name	
Attorney Docket Number	0100.0001320

FEE CALCULATION (continued)

3. ADDITIONAL FEES

Fee Code	Entity Fee (\$)	Fee Code		Fee Description	Fee Paid
105	130	205	65	Surcharge - late filing fee or oath	
127	50	227	25	Surcharge - late provisional filing fee or cover sheet	
139	130	139	130	Non-English specification	
147	2,520	147	2,520	For filing a request for reexamination	
112	920*	112	920*	Requesting publication of SIR prior to Examiner action	
113	1,840*		1,840*	Requesting publication of SIR after Examiner action	
115	110	215	55	Extension for reply within first month	
116	380	216	190	Extension for reply within second month	
117	870	217	435	Extension for reply within third month	
118	1,360		680	Extension for reply within fourth month	
128	1,850		925	Extension for reply within fifth month	
119	300	219	150	Notice of Appeal	
120	300	220	150	Filing a brief in support of an appeal	
121	260	221	130	Request for oral hearing	
138	1,510	138	1,510	Petition to institute a public use proceeding	
140	110	240	55	Petition to revive - unavoidable	
141	1,210	241	605	Petition to revive - unintentional	
142	1,210	242	605	Utility issue fee (or reissue)	
143	430	243	215	Design issue fee	
144	580	244	290	Plant issue fee	
122	130	122	130	Petitions to the Commissioner	
123	50	123	50	Petitions related to provisional applications	
126	240	126	240	Submission of Information Disclosure Stmt	
581	40	581	40	Recording each patent assignment per property (times number of properties)	40.00
146	690	246	345	Filing a submission after final rejection (37 CFR 1 129(a))	
149	690	249	345	For each additional invention to be examined (37 CFR 1 129(b))	
Other					
(spec					
Other (spec					1

Reduced by Basic Filing Fee Paid

SUBTOTAL (3) (\$) 40.00

SUBMITTED BY:	MARKISO	Complete (if applicable)				
Typed or Printed N	Name J	John R. Garrett			Reg. Number	27,888
Signature	John	R Daniel	Date	7/29/00	Deposit Account User ID	50-0441

15

20

FILING OF A UNITED STATES PATENT APPLICATION

In the United States Patent and Trademark Office

Title:

METHOD AND APPARATUS FOR POSTING MULTIPLE VIDEO ADAPTERS

Inventors:

Terry M. Laviolette	Vladimir F. Giemborek
41 Auburn Lane	112 Sweet Water Crescent
Courtice, Ontario, Canada	Richmond Hill, Ontario, Canada
Francis Kwok-To Chan	Adrian Muntianu
21 Elmfield Crescent	8 Roanoke Road, Apt. 602
Scarborough, Ontario, Canada	Toronto, Ontario, Canada

Attorney of Record John R. Garrett Registration No. 27,888

P.O. Box 06229

Wacker Drive Chicago, Illinois 60606-0229

Phone (312) 939-9800 Fax (312) 939-9828

Express Mail Label No. EL504284831US

Date of Deposit.

I hereby certify that this paper is being deposited with the U.S. Postal Service "Express Mail Post Office to Addresses" service under 37 C.F.R. Section 1.10 on the 'Date of Deposit', indicated above, and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

Name of Depositor: Rosalie Swanson (print or type)

Isolie Filmon

PATENT APPLICATION 0100.0001320

METHOD AND APPARATUS FOR POSTING MULTIPLE VIDEO ADAPTERS

5

Field Of The Invention

The present invention relates in general to initialization of computer equipment, and in particular to the POST (power on self test) of multiple video adapters in laptop type computers.

10

15

20

25

30

Background Of The Invention

It is well known in the art that when a typical computer is turned on, the computer executes a self test program referred to as POST. The program is the BIOS (basic input/output system) that is burned into a ROM chip. The BIOS gives the computer a starter mechanism to run the rest of the software from a floppy disk and/or a hard disk. The BIOS is responsible for booting the computer by providing a basic set of instructions. It performs all the tasks that need to be done at start up time. The BIOS also supplies for the operating system an interface to the underlying hardware of the computer in the form of a library of interrupt handlers.

When the system is powered on, the BIOS performs diagnostics and initializes system components, including the video system. This is commonly referred to as POST. Afterwards, the computer will proceed to its final boot up stage by calling the operating system.

Computer systems are known in prior art that are able to simultaneously operate a plurality of display devices, such as CRT displays and LCD displays. Such computers may have multiple video adapters or may have a dual CRT Controllers graphics card.

The multiple displays are used for simultaneously running multiple applications. Under

The multiple displays are used for simultaneously running multiple applications. Under the Windows 98 operating system this concept is known as extended desktop wherein

10

15

20

25

the cursor can drag an icon, file, etc. from the screen of one display device to the screen of another display device. A dual CRT Controllers graphics card is used to operate the two screens of the displays.

Under Windows 98 operating systems, it is possible to operate four displays, which, for example, can be run from a first dual CRT Controller graphics card, and the other two from a second dual CRT Controller graphics card. In this case, the computer system has multiple display adapters. Whatever the configuration, it has become an accepted and desired feature for a computer to have the ability to interface with and operate multiple video adapters for simultaneously running multiple display devices.

With the release of the Windows 2000 operating system and especially in the portable or laptop computer environment, it was found that it was no longer possible to support multiple video adapters if any of the video adapters has compressed Video BIOS. For multiple video cards to operate, it is desirable that all of the Video BIOSs be initialized during POST. However, the Windows 2000 operating system is not capable of doing this. Under the Windows 2000 operating system only the primary video adapter is POSTed. Although this primary video adapter could be a dual CRT Controller graphics card for running two display devices, it is not possible to use an add-on video graphics card with an onboard or built in video adapter. Many motherboards for computers have video adapters built into and stored on the motherboard. That is, the video BIOS is stored in compressed form in a ROM chip on the motherboard.

Portable computers, such as laptops, typically have the video BIOS stored in compressed form on the motherboard. If, however, an add-on video card is used, and if this add-on video card is designated as the primary adapter, the video adapter on the motherboard becomes the secondary video adapter and under the Windows 2000 operating system it is no longer available for use after the POST by the System BIOS.

There is a need for a method and apparatus for executing a POST for each Video BIOS for a computer in which the computer system is capable of operating multiple

video adapters. That is, there is a need for operating multiple display devices for multiple displays under the Windows 2000 operating system, especially for laptop computers.

Brief Description Of The Drawings

5

10

15

The features of the present invention which are believed to be novel are set forth with particularity in the appended claims. The invention, together with further objects and advantages, must be understood by reference to the following description taken in conjunction with the accompanying drawings in the several figures of which like reference numerals identify like elements.

- FIG. 1 schematically depicts a computer environment for use with the present invention.
- FIG. 2 schematically depicts execution of a POST of a computer system using the present invention.
 - FIG. 3 is a flowchart depicting the steps in the method of the present invention.

Detailed Description Of a Preferred Embodiment of The Invention

20

25

30

In the following, the term "secondary adapter" means non-VGA, and the frame buffer may be part of system memory or may be a physically separate memory (ram, harddisk, etc).

Generally, the present invention is a computer system for operating a plurality of display devices. Such a computer system has at least a first video adapter with a first video BIOS and a second video adapter with a second video BIOS. A system BIOS identifies one of the first and second video adapters as a primary video adapter and the other of the first and second video adapters as a secondary video adapter. During POST, the system BIOS stores the first video BIOS in a first memory area in a system memory of the computer. The system BIOS or the Video BIOS then copies the first video BIOS to a second memory area (i.e. frame buffer) when the first video adapter is the second video adapter is the primary video adapter, and POSTs the second video BIOS in the first

memory area. This then causes the first video BIOS in the first memory area to be overwritten by the second video BIOS. On loading a video driver for the first video adapter, the video driver copies the first video BIOS from the second memory area to a third memory area in the system memory.

The present invention is particularly useful for operating multiple display devices, such as CRT devices 100 and 102 in FIG. 1. In this computer system, a portable computer or laptop 104 has an LCD display device 106. As is known in the art, the laptop 104 can be inserted into a docking station 108. The laptop 104 interfaces with the docking station 108 through electrical connectors 110. The CRT type display devices 100 and 102 are connected to the docking station 108.

The laptop computer has a motherboard with the first video adapter and has a first video BIOS stored in a ROM on the motherboard. For example, the laptop computer may contain a RAGE TM LT PRO, manufactured by ATI Technologies Inc. This is a high performance 2D, 3D, and DVD graphics accelerator for AGP and PCI notebooks. For laptop computers the video BIOS is stored in compressed form. The docking station has in this embodiment an add-on board with the second video adapter and the second video BIOS. Typically, the add-on board has the second video BIOS stored in an uncompressed form. The add-on video card in the docking station 108 typically has an application-specific integrated circuit (ASIC) which is a graphics chip that is able to perform at a higher level than the video adapter on the motherboard of the laptop 104. For example, the video card in the docking station 108 could be a dual CRT Controller video card, which can simultaneously operate both display devices 100 and 102. Alternatively, the docking station could have a video card, such as, the RAGE TM XL manufactured by ATI Technologies Inc. This is a high performance video card that provides superior 3D acceleration and comprehensive 3D support.

It is also possible to have a configuration, wherein the laptop computer has a dual display feature. In fact, laptop computers that have the ATI RAGE TM MOBILITY 128 graphics chip, manufacture by ATI Technologies Inc., has a Tri-View architecture that

10

15

20

25

30

allows the video output to be directed to any three of the LCD, TMDS, CRT and TV displays simultaneously. Dual display makes use of a second, independent controller within the graphics chip to display different images on any two of its supported outputs. This is the feature which is supported by Windows 98 operating systems, but not by Windows 2000 operating systems.

Although under the Windows 2000 operating system it is possible to operate both display devices 100 and 102 with a dual CRT Controller video card in the docking station 108, it would not be possible to simultaneously utilize the LCD screen 106 of the laptop 104 with the display devices 100 and 102. This is because, the video BIOS for the video adapter on the motherboard remains compressed and not POSTed and is not available to the video drivers associated with the video adapter on the motherboard. The present invention overcomes this deficiency in the Windows 2000 operating system by providing a modified POST that has minimal impact on the system BIOS and minimal impact on associated video drivers.

FIG. 2 schematically depicts the POST of a computer system which has a motherboard 200 with a ROM 202 which contains the system BIOS 208 and the video BIOS in compressed form for a first video adapter 203. The computer system also has an add-on card 204, which has a ROM 206 that has an uncompressed video BIOS for a video adapter 207 on the video card 204. During POST the System BIOS 208 on the motherboard 200 decompresses the motherboard video BIOS and stores it in a first memory location 210 in system memory 212. When the video adapter 203 on the motherboard 200 is a secondary video adapter and the second video adapter on the add-on video card 204 is the primary video adapter, the System BIOS or Video BIOS 208 then copies the uncompressed and POSTed video BIOS for the first video adapter 203 on the motherboard into second memory area 214 (i.e. frame buffer) ... Although the uncompressed video BIOS of the motherboard can be copied to other locations in the system memory, the frame buffer is easily addressed by the video system of the computer. The uncompressed video BIOS of the add-on video card 204 is then copied and stored in the first memory area 210, which overwrites the video BIOS of the

motherboard which was stored there. The video driver for the video adapter 203 on the motherboard 200 can now copy the uncompressed Video BIOS from the motherboard from the (second memory area 214 into a third memory area 216 where it can be utilized for ongoing operation of the computer system. It should be understood that the present invention can be extended so that second and third add-on video cards, for example, could be utilized in the computer system. Although the embodiment of the present invention is depicted in the setting of a laptop computer connected to a docking station, other various configurations and combinations of computer equipment and add-on video cards could also be utilized with the present invention.

FIG. 3 is a flow diagram depicting operation of the present invention. In the first step 300 the computer system is initialized by the system BIOS and the power on self test (POST) is executed. Thereafter, in step 302 the video adapters, for example on the motherboard and on the add-on card, are identified as a primary video adapter and a secondary video adapter. In step 304 the first video BIOS is decompressed and stored in a first memory area of the system memory. In step 306, POST occurs for the first video BIOS on the motherboard.

If, in step 308, it is determined that the first video adapter on the motherboard is the primary video adapter, then the POST continues on to finish in step 320. If, however, the first video is the secondary video adapter, then the uncompressed first video BIOS is copied from the first memory area into the second memory area (i.e. frame buffer) in step 312. The frame buffer is the portion of memory reserved for holding the complete bit-mapped image that is sent to the display device. In step 314 the second video BIOS is stored in the first memory area of system memory, thereby overwriting the previously stored first video BIOS. In step 316 the POST operation continues for the second video BIOS on the add-on video card. In step 318, the first video BIOS is copied by the driver from the second memory area, i.e. frame buffer to a third memory area of the system memory for use by the video driver for the first video adapter on the motherboard. Finally, the POST goes on to finish in step 320.

10

Thus, the present invention overcomes the deficiency in the prior art (for example, Windows 2000 operating system) by providing a method and apparatus for operating a plurality of display devices with multi-video adapters. It is also accomplished with the least impact on presently existing system BIOS and on associated drivers. The present invention is not limited to the particular details of the apparatus and method depicted and other modifications and applications are contemplated. Certain other changes may be made in the above-described method and apparatus without departing from the true spirit and scope of the invention herein involved. For example, the present invention is not limited to laptop computers, but can be utilized in any type of computer equipment. Also, the present invention could be utilized with operating systems other than the Windows 2000 operating system. It is intended, therefore, that the subject matter of the depicting shall be interpreted as illustrative and not in a limiting sense.

Claims

WHAT IS CLAIMED IS:

A computer system for operating a plurality of display devices, comprising:

at least a first video adapter with a first video BIOS and video driver, and
a second video adapter with a second video BIOS;

a processing unit;

a system memory operatively coupled to the processing unit;

10

a read only memory operatively coupled to the processing unit, the read only memory storing a system BIOS that, when read by the processing unit, causes the processing unit to identify one of the first and second video adapters as a primary video adapter and the other of the first and second video adapters as a secondary video adapter;

15

the processing unit, as directed by the system BIOS, executing a POST (power on self test) during which the system BIOS stores the first video BIOS in a first memory area in a system memory of the computer system, and copies the first video BIOS to a second memory area in the system memory, when the first video adapter is the secondary video adapter and the second video adapter is the primary video adapter, thereafter the second video BIOS being stored in the first memory area, thereby overwriting the first video BIOS in the first memory area; and

20

a video driver for the first video adapter, the video driver copying the first video BIOS from the second memory area to a third memory area in the system memory;

25

wherein the computer system uses at least one of the first and second video adapters to display information on at least one display device connected to the computer.

30

2. The computer system according to claim 1, wherein the computer system further comprises a motherboard, the motherboard having stored thereon the first video BIOS and the first video adapter.

- 3. The computer system according to claim 2, wherein the computer system further comprises a motherboard, the motherboard having stored thereon the first video BIOS and the first video adapter, wherein the computer system further comprises an add-on board, the add-on board having stored thereon the second video BIOS, wherein the first video BIOS is stored on the motherboard in compressed form, and wherein the first video BIOS is stored in the first memory area in decompressed form.
- The computer system according to claim 1, wherein the computer system further comprises an add-on board, the add-on board having stored thereon the second video BIOS.
 - 5. The computer system according to claim 1, wherein the second video BIOS is stored in uncompressed form.
 - 6. The computer system according to claim 1, wherein the computer system comprises a portable computer having the first video adapter and a docking station for receiving the portable computer, the docking station having the second video adapter.
 - 7. The computer system according to claim 6, wherein the portable computer has a first display device, and wherein a second display device is operatively connected to the docking station.

8. The computer system according to claim 7, wherein the first video adapter provides display data to the first video device, and wherein the second video adapter provides display data to the second video device.

25

9. The computer system according to claim 1, wherein the computer system further comprises a frame buffer operatively connected to the processing unit, and wherein the second memory is the frame buffer.

10. A computer system for operating a plurality of display devices, comprising:

a motherboard, the motherboard having a first video adapter with a first video BIOS and a video driver, the first video BIOS being stored on the motherboard in compressed form;

an add-on board, the add-on board having a second video adapter with a second video BIOS, the first video BIOS being stored in the first memory area in decompressed form;

a system memory having a plurality of memory areas;

the motherboard of the computer system, having stored thereon a system BIOS that, during a POST of the computer system, identifies the second video adapter as a primary video adapter and the first video adapters as a secondary video adapter;

the system BIOS structured to decompress the first video BIOS and storing the decompressed first video BIOS in a first memory area in a system memory of the computer, to copy the decompressed first video BIOS to a second memory area in the system memory, and thereafter to store the second video BIOS in the first memory area, thereby overwriting the first video BIOS in the first memory area;

the video driver structured to copy the first video BIOS from the second memory area to a third memory area in the system memory;

wherein the computer system uses at least one of the first and second video adapters to display information on at least one display device connected to the computer.

25 11. The computer system according to claim 10, wherein the computer system comprises a portable computer containing the motherboard with the first video adapter and a docking station for receiving the portable computer, the docking station containing the add-on board with the second video adapter.

15

5

10

- 12. The computer system according to claim 11, wherein the portable computer has connected thereto the first display device, and wherein the second display device is operatively connected to the docking station.
- The computer system according to claim 10, wherein the first video adapter provides display data to at least the first video device, and wherein the second video adapter provides display data to at least the second video device.

10

15

30

14. A method for posting a computer system having at least a first video adapter with a first video BIOS and a second video adapter with a second video BIOS, comprising the steps of:

initializing a system BIOS of the computer system;

identifying the second video adapter as a primary video adapter and the first video adapter as a secondary video adapter;

posting the first video BIOS;

storing the first video BIOS in a first memory area in a system memory of the computer;

copying the first video BIOS to a memory area;

posting the second video BIOS;

storing the second video BIOS in the first memory area, thereby overwriting the first video BIOS in the first memory area;

loading a video driver for the first video adapter;

copying the first video BIOS from the video frame buffer area to a further memory area in the system memory;

using at least one of the first and second video adapters to display information on at least one display device connected to the computer.

- 20 15. The method according to claim 14, wherein the computer system comprises a motherboard, the motherboard having stored thereon in compressed form the first video BIOS.
- The method according to claim 15, wherein the system BIOS, during POST,
 decompresses first video BIOS, and stores the decompressed first video BIOS in the first memory area of the system memory.
 - 17. The method according to claim 14, wherein the computer system has an add-on board, the add-on board having stored thereon the second video BIOS in uncompressed form.

18. The method according to claim 14, wherein the computer system comprises a portable computer having the first video adapter and a docking station for receiving the portable computer, the docking station having the second video adapter.

5

19. The computer system according to claim 18, wherein the portable computer has a first display device, and wherein at least a second display device is operatively connected to the docking station, the first video adapter providing display data to the first video device, and the second video adapter providing display data to the second video device.

10

20. The method according to claim 14, wherein the computer system has a plurality of video adapters and respectively associated display devices.

METHOD AND APPARATUS FOR POSTING A COMPUTER HAVING MULTIPLE VIDEO ADAPTERS

Abstract Of The Invention

5

10

The computer system for operates a plurality of display devices 100 and 102. Such a computer system has at least a first video adapter 203 with a first video BIOS and a second video adapter 207 with a second video BIOS. A system BIOS identifies one of the first and second video adapters 203, 207 as a primary video adapter and the other of the first and second video adapters 203, 207 as a secondary video adapter. During POST, the system BIOS stores the first video BIOS in a first memory area 210 in a system memory 212 of the computer. The system BIOS or Video BIOS then copies the first video BIOS to a second memory area 214 in the system memory 212 when the first video adapter 203 is the secondary video adapter. The system BIOS POSTs the second video BIOS when the second video adapter 207 is the primary video adapter, and stores the second video BIOS in the first memory area 210. This then causes the first video BIOS in the first memory area 210 to be overwritten by the second video BIOS. On loading a video driver for the first video adapter 203, the video driver copies the first video BIOS from the second memory area 214 to a third memory area 216 in the system memory 212.

20






Fig. 1





DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION

(37 CFR 1.63)

	X	Declaration	Submitted	with	Initial	Filing,	OR
ĺ		Declaration	Submitted	after	Initial	Filing	
(su	rcharge (37	CFR 1.16 (e)) re	quired)	

Attorney Docket Number 0100.0001320 First Named Inventor Terry M. Laviolette COMPLETE IF KNOWN Application Number Filing Date Group Art Unit **Examiner Name**

As a below na	med inventor.	, I bereby	declare that:
---------------	---------------	------------	---------------

Мy	residence,	post office a	address,	and	citizensh	ip are	as s	tated	belov	v next	to 11	iy nam	lĈ.
----	------------	---------------	----------	-----	-----------	--------	------	-------	-------	--------	-------	--------	-----

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: Method and Apparatus for Posting a Computer Having Multiple Video Adapters the specification of which:

ATI Technologies Inc.

is attached l	hereto.			
was file on	(MM/DD/YYYY)	as United States	Application Number or PCT	International Application
Number	and was amended on (M	M/DD/YYYY)	(if applicable).	

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign	Country	Foreign Filing Date	•	Certified Copy Attached?
Application Number(s)		(MM/DD/YYYY)	Claimed	YES NO

Additional foreign application numbers are fisted on a supplemental priority data sheet PTO/SB/02B attached hereto.

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States	s provisional application(s) listed below.
Application Number(s)	Filing Data (MM/DD/YYYY)
Additional provisional application numbers are listed on a supple	mental priority data sheet PTO/SB/02B attached hereto.

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the

United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)
		1411

Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Name	Registration Number	Name	Registration Number
John R. Garrett	27,888	Christopher J. Reckamp	34,414
Paul M. Anderson	39,896	Ross D. Snyder	37,730
Sally Daub	41,478		

Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to:

Markison & Reckamp, P.C. P.O. Box 06229 Wacker Drive Chicago, Illinois 60606-0229 Telephone:312-939-9800 Facsimile: 312-939-9828

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor: A petition has been filed for this unsigned inventor								
Giver	1 Name (fir	rst and middle	e [if any])				Name or Surname	
Terry M.				جمرا	iiobette	aviole	He	
Inventor's Signature	(MIlm	r M			Date	7/17/2000	
Residence	City: Coal	rtice	State	: Ontario	Country	: Canada	Citizenship: Canada	
Post Office	Address	41 Auburn	Lane					
City: Court	ice		State: Onto	rio	ZIP: L1E	2C3	Country: Canada	
		oint Inventorst and middle		A	petition ha		for this unsigned inventor Name or Surname	
Vladimir F.			Gie	mborek				
Inventor's	411	ilea	. a			Date	7/24/2000	
Signature	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		~~~	<u> </u>			1/27/2000	
Signature Residence				: Ontario	Country	Canada	Citizenship: Canada	
Residence	City: Rich		State		Country	: Canada		
Residence Post Office	City: Ricl Address	mond Hill	State	ent	Country			
Residence Post Office City: Richn Name of Ad	City: Rich Address lond Hill ditional J	mond Hill	State Vater Cresc State: Onta	ent rio	ZIP: L4S	2B4 s been filed	Citizenship: Canada	
Residence Post Office City: Richn Name of Ad	City: Rich Address nond Hill ditional J	amond Hill 112 Sweet V	State Vater Cresc State: Onta	ent rio	ZIP: L4S	2B4 s been filed	Country: Canada Country: Canada for this unsigned inventor	
Residence Post Office City: Richm Name of Ad Giver	City: Rich Address nond Hill ditional J	amond Hill 112 Sweet V	State Vater Cresc State: Onta	rio A	ZIP: L4S	2B4 s been filed	Country: Canada Country: Canada for this unsigned inventor	-V 1 %-1 h.d.
Residence Post Office City: Richn Name of Ad Giver Francis Kw Inventor's	City: Rich Address nond Hill ditional J	oint Inventorst and middle	State Water Cresc State: Onta r: e [if any])	rio A	ZIP: L48 petition ha	2B4 s been filed Family	Country: Canada Country: Canada for this unsigned inventor Name or Surname	
Residence Post Office City: Richn Name of Ad Giver Francis Kw Inventor's Signature	City: Rich Address nond Hill ditional J n Name (fin ok-To	oint Inventorst and middle	State Water Cresc State: Onta r: e [if any]) State	ent rio A	ZIP: L48 petition ha	2B4 s been filed Family	Country: Canada Country: Canada for this unsigned inventor Name or Surname	-V

Additional inventors are being named on the 1_supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto.



PTO/SR/02A (3-97)

DECLARATION

ADDITIONAL INVENTOR(S) Supplemental Sheet Page 1 of 1

Name of Additional Joint Inventor:				A perition has been theu for this ansigned inventor				
Giver	n Name (fi	rst and middle	= [if/ / my])	Family Name or Surname				
Adrian		//		Mutia	ınu 💮			
Inventor's		//	X			Date	28 Sory 6	د ک
Signature		Mes	<u> </u>		<u>, </u>			
			State: On	tario <u> </u>	Country:	Canada	Citizenship: Canada	
Post Office	8 Roznoke	Road Apt. 602						
City: Toron	ıto		State: Ontario		ZIP: M3A	1E6	Country: Canad	<u>a</u>
		oint Lavento		<u> </u>	etition has		for this unsigned invento	r
Give	n Name (fi	rst and middle	e [if any])			Family	Name or Surname	
							AIN	
Inventor's	T					Date		
Signature								
Residence	City:		State:		Country:		Citizenship:	
Post Office Address								
City:			State:		ZIP:		Country:	
<u> </u>								
		oint Invento		☐ A p	etition has		for this unsigned invento	<u>r</u>
Give	n Name (fi	rst and middle	e [if any])			Family	Name or Surname	
Inventor's						Date		
Signature								
Residence	City:		State:		Country:		Citizenship:	
Post Office	Address							
City:			State:		ZIP:		Country:	
Name of Ac	. Isroitibh	ioint Invento	r:	ПАр	etition has	been filed	for this unsigned invento	r
		rst and middl		1			Name or Surname	
			- 1					
Inventor's			······································			Date		
	1				1			
1						I		
Signature	City:		State:	············	Country:		Citizenship:	
1	<u> </u>		State:		Country:		Citizenship:	